

UNCLASSIFIED

AD NUMBER

AD444071

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; JUL 1964. Other requests shall be referred to Army Missile Command, Redstone Scientific Information Center, Redstone Arsenal, AL.

AUTHORITY

rsic ltr, 5 jan 1966

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 4 4 4 0 7 1

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

444071

CATALOGED BY DDC

AS AD No.


444071

CONTRACT TECHNICAL NOTE

THE RADAR ABSORPTION EFFECT CAUSED BY VERY THIN PLASMA SHEATHS

H.M. MUSAL, JR. AND W.E. BLORE

CONTRACT NO. DA-04-495-ORD-3567(Z)
HYPERVELOCITY RANGE RESEARCH PROGRAM
A PART OF PROJECT "DEFENDER"



GM DEFENSE RESEARCH LABORATORIES

SANTA BARBARA, CALIFORNIA



AEROSPACE OPERATIONS DEPARTMENT



CTN64-02

JULY 1964

NOTICE

The information presented in this Technical Note is preliminary and should not be interpreted as representing the final opinion of GM Defense Research Laboratories or the author on the subject. Further, to expedite prompt distribution of the technical contents, no attempt at an editorial review has been made.

CONTRACT TECHNICAL NOTE

**THE RADAR ABSORPTION EFFECT CAUSED BY
VERY THIN PLASMA SHEATHS**

H.M. MUSAL, JR. AND W.E. BLORE

THIS RESEARCH WAS SUPPORTED BY THE
ADVANCED RESEARCH PROJECTS AGENCY

AND WAS MONITORED BY THE
U.S. ARMY MISSILE COMMAND
REDSTONE ARSENAL, ALABAMA

GM DEFENSE RESEARCH LABORATORIES

SANTA BARBARA, CALIFORNIA



AEROSPACE OPERATIONS DEPARTMENT

CONTRACT NO. DA-04-495-ORD-3567(Z)
HYPERVELOCITY RANGE RESEARCH PROGRAM
A PART OF PROJECT "DEFENDER"

CTN64-02

JULY 1964

DDC AVAILABILITY NOTICE

Qualified requesters may obtain
copies of this report from DDC

This report is a reprint of a paper presented at the 17th AMRAC (Anti-Missile Research Advisory Council) meeting held at the United States Naval Postgraduate School in Monterey, California, on 27-29 April 1964, sponsored by ARPA (Advanced Research Projects Agency).

THE RADAR ABSORPTION EFFECT CAUSED BY VERY THIN PLASMA SHEATHS

ABSTRACT

The radar absorption effect has been observed in full scale reentry vehicle tests and in laboratory and field studies of hypersonic vehicle flow field observables. The usual manifestation of this effect is the drastic reduction of the radar cross section of the vehicle and its associated flow field under certain conditions. Ballistic range studies of this effect have shown significantly large absorption to occur for even very thin plasma sheaths. This is inexplicable in terms of the theory that explains the full scale vehicle results. A more advanced theory is presented here, which has the potential for explaining the anomalous absorption caused by very thin plasma layers covering blunt metallic bodies. In essence, it is shown that the anomalous absorption may be a diffraction effect caused by the gradient of the electron density in the plasma sheath around the body. That is, the effect occurs when the body is only partially covered by an overdense plasma sheath. This plasma layer can be very thin compared to the wavelength of the radar wave and still cause a significant decrease in

the radar cross section. These results are illustrated by several theoretical graphs that show the dependence of the radar cross section of a metal sphere partially covered by a plasma layer on the size, thickness and properties of the layer. Finally, this theory is applied to predict the anomalous absorption observed in ballistic range studies. The large amount of absorption observed experimentally is correctly predicted by this theory, but an accurate verification of all the details of the behavior as a function of ambient air density and body speed awaits more extensive and detailed flow field computations.

THE RADAR ABSORPTION EFFECT CAUSED BY VERY THIN PLASMA SHEATHS

INTRODUCTION

The radar absorption effect has been observed in full-scale reentry events, in small-scale field tests, and in laboratory studies. The usual manifestation of the radar absorption effect is the drastic reduction of the radar cross section of the vehicle and its surrounding flow field under certain flight conditions. The decrease in radar cross section is of the order of 10 to 20 db. This effect has been observed in two different flight regimes. It has been observed at high altitudes during reentry of the MIT Trailblazer Vehicle⁽¹⁾. It has also been observed at relatively low altitudes during the reentry of full-scale reentry vehicles⁽²⁾. The laboratory observations of this phenomenon have been at relatively high ambient air densities and low velocities, which corresponds to the low-altitude observations in the full-scale situation. These observations have been made at GM DRL⁽³⁾ and at CARDE⁽⁴⁾.

Several attempts to explain the radar absorption effect have been made. In the case of the full-scale observations, these have been explained qualitatively and quantitatively by Musal⁽⁵⁾. This was done on the basis of a simple geometrical optics approach. Radar wave

destructive interference and real power absorption in the plasma sheath surrounding the nose cone was shown theoretically to give rise to the amount of absorption, and the altitude at which it occurred, actually measured during the reentry. In this situation the thickness of the plasma sheath was of the order of one-half the wavelength of the radar wave. This is approximately the minimum thickness for which the simple geometrical optics explanation will predict large amounts of absorption. In the case of the MIT Trailblazer experiments, Murphy⁽¹⁾ has offered an explanation for the high altitude radar absorption which occurs at relatively high velocities. His explanation is based on the fact that the plasma layer surrounding the vehicle may be much thicker than the shock stand-off distance because of ultraviolet photoionization of the air in front of the shock. This effectively creates a large cloud of low density ionization around the vehicle. There is also gradual radial gradient of the electron density in this cloud. At the radar frequency used in this experiment, a strong interaction between the wave and the ionization cloud was experienced. The net effect was to decrease the backscattering from the entire structure. The ballistic range experimental results obtained at GM DRL and at CARDE are not explainable by either the simple geometrical optics approach or by means of the photoionization assumption. The first explanation is not

applicable because the shock layer is too thin. Calculations have shown that in order to predict the amount of absorption experimentally observed, it would be necessary to assume that the shock layer was three times as thick as was actually measured. The possibility that photoionization would contribute toward a larger ionization cloud around the body was disproved by measurements of the amount of precursor ionization outside of the shock front. This was done in a series of measurements at GM DRL⁽⁶⁾.

In order to explain the absorption effect for the thin plasma sheaths that are present in the ballistic range measurements several other mechanisms were investigated. The possibility that the angular gradient of the electron density around the body might cause focusing or defocusing effects was investigated. Using a geometrical optics approach, Musal⁽⁷⁾ showed that the refractive effect of the gradient can cause significant focusing and defocusing of the backscattered radar wave. However, it was shown that in order to predict significantly large amounts of absorption by this mechanism, the plasma layer again had to be approximately two or three times as thick as was measured.

The angular gradient in electron density can be considered from another viewpoint. This is the diffractive aspect of such a non-uniform layer. The results of this approach will be outlined here since they appear to contain the basic elements for the explanation of the radar

absorption effect caused by very thin plasma layers on metallic bodies.

THEORY

A theory that appears to offer a possible explanation for large decreases in the radar cross section of a metallic body when it is partially covered by a thin plasma layer is presented here. This theory depends on the diffractive effect of angular gradients in the plasma layer around the body, and predicts large decreases in radar cross section caused by very thin plasma layers.

The radar cross section of a body can be predicted theoretically in exact form if the tangential components of the electric and magnetic fields induced on the surface of the body by the incident radar wave are known exactly (see for example, Mentzer⁽⁸⁾). In the practical situation, the exact fields are usually not known. Thus some approximate method must be used to obtain approximate values of these fields when the body and the incident wave are specified. The well-known physical optics approximation is often used when the body is metallic. In essence, this approximation takes for the tangential induced fields on the surface of the body a magnetic and an electric field which are just equal and opposite, respectively, to the tangential components of the magnetic and electric fields of the incident wave. A suitable integration of these

fields over the illuminated surface of the body then gives the far field scattered wave intensity, from which the radar cross section is determined. In order to extend this theory to the case of plasma covered metallic bodies, it has been assumed that the effect of the plasma layer is merely to change the phase and amplitude of these induced fields. If the layer is very thin this appears to be a reasonably valid approximation. The far field scattered wave is then computed in the same manner as in the usual physical optics approach.

When this technique is applied to the case of a metal sphere covered by a thin plasma layer the resultant integral for the nose-on backscattering radar cross section (σ) can be shown to be

$$\frac{\sigma}{\lambda^2} = \frac{\pi^3 a^2}{4 \lambda^2} \left| \int_{x=0}^{x=4a/\lambda} (\Gamma_{TM} - \Gamma_{TE}) \left(1 - \frac{x\lambda}{4a}\right) e^{j4\pi \frac{h}{\lambda}} e^{-j\pi x \left(1 + \frac{h}{a}\right)} dx \right|^2$$

where Γ_{TM} and Γ_{TE} are the TM and TE mode reflection coefficients for a metal-backed plasma layer, given by

$$\Gamma_{TM} = \frac{\Gamma_{PTM} + e^z}{1 + \Gamma_{PTM} e^z}$$

$$\Gamma_{TE} = \frac{\Gamma_{PTE} - e^Z}{1 - \Gamma_{PTE} e^Z}$$

where Γ_{PTM} and Γ_{PTE} are given by

$$\Gamma_{PTM} = \frac{\left(1 - \frac{\Omega_p^2}{1-j\Omega_c}\right)\left(1 - \frac{x\lambda}{4a}\right) - \left[\left(1 - \frac{x\lambda}{4a}\right)^2 - \frac{\Omega_p^2}{1-j\Omega_c}\right]^{1/2}}{\left(1 - \frac{\Omega_p^2}{1-j\Omega_c}\right)\left(1 - \frac{x\lambda}{4a}\right) + \left[\left(1 - \frac{x\lambda}{4a}\right)^2 - \frac{\Omega_p^2}{1-j\Omega_c}\right]^{1/2}}$$

$$\Gamma_{PTE} = \frac{\left(1 - \frac{x\lambda}{4a}\right) - \left[\left(1 - \frac{x\lambda}{4a}\right)^2 - \frac{\Omega_p^2}{1-j\Omega_c}\right]^{1/2}}{\left(1 - \frac{x\lambda}{4a}\right) + \left[\left(1 - \frac{x\lambda}{4a}\right)^2 - \frac{\Omega_p^2}{1-j\Omega_c}\right]^{1/2}}$$

and Z is given by

$$Z = -j \frac{4\pi h}{\lambda} \left[\left(1 - \frac{x\lambda}{4a}\right)^2 - \frac{\Omega_p^2}{1-j\Omega_c}\right]^{1/2}$$

and λ is the radar wavelength, a is the radius of the sphere, and h is the thickness of plasma layer. The plasma properties are given by the normalized plasma frequency Ω_p and the normalized electron collision frequency Ω_c , which are

$$\Omega_p = \frac{\omega_p}{\omega} = \frac{1}{\omega} \left(\frac{q^2 N}{\epsilon m} \right)^{1/2}$$

$$\Omega_c = \frac{\nu_c}{\omega}$$

where ω is the radar angular frequency ($2\pi f$), ν_c is the electron collision frequency, ω_p is the plasma frequency, q is the electric charge carried by an electron and m is its mass, N is the electron number density, and ϵ is the capacitivity of free-space. It can be shown that if the reflection coefficients of the layer are not functions of the angle of incidence, then the above integral can be explicitly evaluated in closed form. This is not the case for a plasma layer. Consequently, the integral must be evaluated by numerical integration.

Some typical results of this approach are shown in Figures 1 and 2. These figures show the radar cross section of a metal sphere as a function of the amount of the sphere covered by a uniform thin layer of plasma. Figure 1 shows the change in the radar cross section as the layer becomes thicker. It can be seen that a layer of only 1/10 of a wavelength in thickness is necessary to give appreciable changes in the radar cross section as the amount of angular coverage is changed. Figure 2 shows the change in the radar cross section as a layer of constant thickness changes in its electron density. A change in electron

density from critical density to 100 times critical density is encompassed.

In order to gain some confidence in the validity of this theory, several experimental measurements have been made involving more controllable configurations and materials. These experimental measurements have shown that the theory is remarkable good, provided that one does not consider bodies which have a large extent of surface nearly parallel to the direction of incidence of the radar wave.

APPLICATION

The diffraction theory will now be applied to the ballistic range experimental situation. A preliminary attempt to predict theoretically the amount of absorption obtained in the GM DRL ballistic range studies of the radar absorption effect is presented here. In order to do this properly, it is necessary to know the spatial variation of the electron density and collision frequency throughout the entire shock layer around the body. The computation of these quantities in the flow field is a very lengthy aerodynamic calculation. The flow field calculation must be repeated at each speed and/or pressure for which the radar cross section is to be calculated. In order to avoid this much extensive work at the present time, we have taken some representative approximate variations

of the flow field properties for use in the preliminary radar cross section calculations. The thickness of the plasma layer was taken to be the thickness of the overdense region of the plasma sheath around the body. The electron density and collision frequency within this overdense region were taken to be the values which existed in the stagnation region for the speed and ambient pressure considered. In order to obtain the dependence of the radar cross section on body speed, the way in which this overdense region thickens and spreads over the body as a function of speed was approximated by extrapolation of limited flow field data⁽⁹⁾. This approach only approximates the actual flow field configuration. Using this approach, the radar cross section was calculated as a function of velocity for the ambient pressure used in the ballistic range studies. The theoretical results are shown in Figure 3, along with the experimental data. It can be seen that a large decrease in the radar cross section, of the order of 15 db, is obtained with the new theory. Previous theories gave approximately 3 db of absorption under these conditions. The details of the fluctuations of the radar cross section at high velocities are probably not significant because the flow field was only approximated and the assumptions that were made were not very good for such a large fractional coverage of the body. As was pointed out earlier, the

theory itself does not appear to be very accurate in this regime either.

The real significance of this theoretical calculation is that a very large decrease in the radar cross section is obtained with only a very thin plasma layer. The details of how the radar cross section varies with speed depend critically on the development of the ionization around the body. Thus there is a need for very good flow field calculations before exact comparisons between the theoretical and experimental results can be made. Work is continuing along the lines of improving the diffraction theory used in the prediction of the radar cross sections of plasma covered metal bodies, and in the calculation of the flow fields around blunt bodies.

CONCLUSIONS

It appears that a theoretical explanation for the large decrease in the radar cross section of a metal body caused by a very thin plasma sheath has been found. The decrease depends on partial coverage of the body by the plasma layer. In other words, it is the angular gradients of the plasma properties around the body that cause severe diffraction of the radar wave. This appears to be the explanation for the anomalous absorption measured in ballistic range studies. This

effect and its theoretical interpretation, when more highly refined, may be useful as a flow field diagnostic technique.

REFERENCES

1. E. L. Murphy, "Photo-Ionized Cloud as Source for Decrease in Backscatter Cross Section of Re-entering Body", Technical Report No. 294, 17 January 1963, Lincoln Laboratory, Massachusetts Institute of Technology, Lexington, Mass.
2. H. M. Musal, Jr., "The Plasma Sheath Effect on the Radar Cross Section During Reentry of Several IRBM Nose Cones", Research Note RN 10 (S), 1 June 1960, Advanced Development Laboratories, Bendix Products Division, South Bend, Ind.
3. H. M. Musal, Jr., P. E. Robillard and R. I. Primich, "Radar Absorption Effects Measured in a Flight Physics Range," Technical Report TR62-209B, December 1962, GM Defense Research Laboratories, General Motors Corporation, Santa Barbara, California. See also AMRAC Proceedings, Vol. VII, Part I, Meeting of 1 and 2 November 1962, Philadelphia, Penn., pp. 97-154.
4. M. Gravel, "Interim Report on the Interaction of Microwaves with the Shock Front of Hypersonic Projectiles", CARDE Technical

Report 466, August 1963, Canadian Armament Research and Development Establishment, Valcartier, P. Q.

5. H. M. Musal, Jr., "Plasma Effects on the Radar Cross Sections of Reentry Objects", Seventh Annual Radar Symposium Record, University of Michigan, Ann Arbor, Michigan, June 1961, pp. 351-373.
6. S. Zivanovic, "Investigation of Precursor Ionization in Front of the Shock Waves of Hypersonic Projectiles", AIAA Conference on Physics of Entry into Planetary Atmospheres, August 26-28, 1963, Massachusetts Institute of Technology, Cambridge, Mass.
7. H. M. Musal, Jr., "On the Theory of the Radar-Plasma Absorption Effect", Technical Report TR63-217 A, July 1963, GM Defense Research Laboratories, General Motors Corporation, Santa Barbara, California.
8. J. R. Mentzer, Scattering and Diffraction of Radio Waves, Macmillan Company, New York, 1955.
9. Cornell Aeronautical Laboratory, Inc., "Nonequilibrium Bow Shock Calculations for Defense Research Laboratories, General Motors Corporation", CAL Order No. 647, 6 December 1962, Buffalo, New York.




FIGURE 1 Radar Cross Section of Plasma Covered Metal Sphere-Effect of Plasma Thickness




FIGURE 2 Radar Cross Section of Plasma Covered Metal Sphere-Effect of Plasma Density




FIGURE 3 Radar Absorption Effect Observed
in Ballistic Range Compared
to Theory

DISTRIBUTION LIST for Analysis Reports on the HYPERVELOCITY RANGE RESEARCH PROGRAM

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Director		U. S. Air Force	
Advanced Research Projects Agency		Ballistic Systems Division	
Washington 25, D. C.		AF Unit Post Office	
ATTN: F. Koether	1 - 3	Los Angeles 45, California	51
ATTN: E. Haynes	4	ATTN: Major W. Levy	52
ATTN: C. McLain	5	ATTN: Lt. K. G. Jefferson	
ATTN: Major J. Kiernan	6	HQ BSD (AFSC)	
		AF Unit Post Office	
Aerojet-General Corporation		Los Angeles 45, California	
P. O. Box 296		ATTN: BSRVD	53
Azusa, California			
ATTN: Technical Library	7	USAF Cambridge Research Laboratories	
		Laurence Hanscom Field	
Aeronutronics Division, Ford Motor Co.		Bedford, Massachusetts	
Ford Road		ATTN: CRRELRL, Stop 29	54
Newport Beach, California			
ATTN: Technical Information Services	8	Director	
ATTN: R. Hoglund	9	USAF Office of Scientific Research	
		Washington 25, D. C.	
Aerospace Corporation		ATTN: Mechanics Division/	55
2400 E. El Segundo Blvd		Major Terrell	
El Segundo, California			
ATTN: Manager of Penetration Aids	10	Director	
		Ames Research Center	
Aerospace Corporation		Moffett Field, California	
P. O. Box 95085		ATTN: H. Allen	56
Los Angeles 45, California			
ATTN: J. Logan	11	Applied Physics Laboratory	
		The John Hopkins University	
Aerospace Corporation		8621 Georgia Avenue	
San Bernardino, California		Silver Spring, Maryland	
ATTN: Mr. R. Fowler	12	ATTN: G. Seielstad	57
ATTN: Mr. Howard Meyers	13-42		
		Applied Physics Laboratory	
Avco-Everett Research Laboratory		Sylvania Elec. Products	
2385 Revere Beach Parkway		Waltham, Massachusetts	
Everett 49, Massachusetts		ATTN: R. Row	58
ATTN: Dr. Bennett Kivel	43		
ATTN: Technical Library	44	Armour Research Foundation	
		10 W. 35th Street	
Avco Research and Advanced Development		Chicago 16, Illinois	
Wilmington, Massachusetts		ATTN: Fluid Dynamics Research	59
ATTN: Dr. A. Pallone	45	Division	
ATTN: Dr. W. E. Gibson	46		
ATTN: Dr. J. Ekerman	47	Commanding General	
		U. S. Army Air Defense Command	
Bell Telephone Laboratories		Colorado Springs, Colorado	
Murray Hill, New Jersey		ATTN: Advanced Projects Division, G-3	60
ATTN: Dr. I. Pelech	48		
ATTN: Dr. S. P. Morgan	49		
ATTN: Dr. S. J. Buchsbaum	50		

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Commanding General U. S. Army Ballistics Research Laboratories Aberdeen Proving Gound, Maryland ATTN: C. H. Murphy ATTN: B. J. Karpov	61 62	Avco Corporation Research and Advanced Development Division Wilmington, Massachusetts ATTN: Technical Library ATTN: Dr. Wentink	76 77
Commanding General U. S. Army Elec. and Communications Command Research and Development Fort Monmouth, New Jersey	63	Special Projects Office Department of The Navy Washington 25, D. C. ATTN: Martin Bloom/SP-272	78
Commanding General U. S. Army Materiel Command Washington 25, D. C.	64	Barnes Engineering Company 30 Commerce Road Stamford, Connecticut ATTN: H. Yates	79
Commander U. S. Army Missile Command Redstone Arsenal, Alabama ATTN: AMSMI-RB ATTN: AMSMI-RRX ATTN: AMSMI-RNR ATTN: AMCPM-ZER-R	65 66 67 68	Battelle Memorial Institute 505 King Avenue Columbus 1, Ohio ATTN: Battelle-DEFENDER	80
Security Office, Army Missile Command Pacific Field Office Box 56, Navy 824 c/o FPO, San Francisco, California ATTN: Dr. S. Edelberg	69	Bell Telephone Laboratories, Inc. Whippany, New Jersey ATTN: C. W. Hoover, Room 2B-105 ATTN: C. E. Paul ATTN: John McCarthy	81 82 83
Commanding General U. S. Army Research and Development Washington 25, D. C. ATTN: Intl. Division ATTN: Physical Sciences Division	70 71	Bendix Corporation Systems Division 3300 Plymouth Road Ann Arbor, Michigan ATTN: Systems Analysis and Math Dept. ATTN: Flight Sciences Department	84 85
Commanding Officer U. S. Army Signal Missile Support Agency White Sands Missile Range, New Mexico ATTN: SIGWS-MM-1 ATTN: MEW	72 73	Boeing Airplane Company P. O. Box 3707 Seattle, Washington ATTN: Org. 2-5732/J. Klaimon	86
U. S. Army Technical Intelligence Agency Arlington Hall Station Arlington 12, Virginia ATTN: ORDLI	74	Brown Engineering Company Huntsville, Alabama ATTN: Technical Library	87
ARO, Inc. von Karman Facility Tullahoma, Tennessee ATTN: J. Lukasiewicz	75	California Institute of Technology Pasadena, California ATTN: Prof. L. Lees	88
		Central Intelligence Agency 2930 E Street, N. W. Washington, D. C. ATTN: OCR Standard Distribution	89-91

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Communication and Propagation Laboratory Stanford Research Institute Menlo Park, California ATTN: Mr. Ray L. Leadabrand, Head	92	Geophysics Corporation of America Burlington Road Bedford, Massachusetts	123
Propagation Group	93	Heliodyne Corporation	124
ATTN: Dr. Carson Flammer		2365 Westwood Blvd Los Angeles 64, California	
Defense Documentation Center	94-113	Institute for Defense Analyses 1666 Connecticut Avenue N. W. Washington 9, D. C.	
Cameron Station		ATTN: Dr. J. Menkes	125
Alexandria, Virginia		ATTN: Dr. L. Biberman	126
Cornell Aeronautical Laboratory		ATTN: Dr. R. Fox	127
4455 Genesee Street		ATTN: Dr. J. Martin	128
Buffalo 21, New York	114	ATTN: Mr. D. Katcher, JASON Library	129
ATTN: J. Lotsof	115		
ATTN: W. Wurster	116	Institute of Science and Technology The University of Michigan P. O. Box 618 Ann Arbor, Michigan	
ATTN: Applied Physics Dept.		ATTN: BAMIRAC Library	130
Defense Research Corporation		Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California	
6300 Hollister Avenue, Goleta, California	117	ATTN: H. Denslow	131
ATTN: W. Short		ATTN: Library	132
Director		Kaman Nuclear Division Colorado Springs, Colorado	
Electromagnetic Warfare Laboratory		ATTN: A. Bridges	133
Wright-Patterson Air Force Base Dayton, Ohio	118	Director Langley Research Center Langley Field, Virginia	
ATTN: ASRN/W. Bahret		ATTN: W. Erickson	134
Electro-Optical Systems, Inc.		ATTN: R. L. Trimpi	135
300 N. Halstead Street Pasadena, California	119	Lockheed Corporation Missiles and Space Division Sunnyvale, California	
ATTN: R. Denison		ATTN: Ray Munson	136
General Applied Sciences Laboratories		Melpar, Inc. Applied Science Division 11 Galen Street Watertown 72, Massachusetts	
Merrick and Stewart Avenues Westbury, Long Island, New York	120	ATTN: Librarian	137
ATTN: M. Bloom			
General Dynamics Corporation			
Astronautics Division San Diego, California	121		
ATTN: Chief Librarian, Mail Zone 6-157			
General Electric Company			
Re-entry Vehicles Division 3198 Chestnut Street Philadelphia, Pennsylvania	122		
ATTN: L. I. Chaseen, Room 3446			

DISTRIBUTION LIST (continued)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
Martin Aircraft Company Orlando, Florida ATTN: J. Mays	138	Purdue University School Aero and Engineering Sciences LaFayette, Indiana ATTN: I. Kvakovsky	151
Director Marshall Space Flight Center Huntsville, Alabama ATTN: M-AERO-TS	139	Radio Corporation of America Missiles and Surface Radar Division Moorestown, New Jersey	152
Massachusetts Institute of Technology Lincoln Laboratory P.O. Box 73 Lexington 73, Massachusetts ATTN: M. Herlin	140	The Rand Corporation 1700 Main Street Santa Monica, California ATTN: Library	153
ATTN: R. Slattery	141	Raytheon Manufacturing Company Missile Systems Division Bedford, Massachusetts	
ATTN: V. Guethlen	142	ATTN: I. Britton, Librarian	154
Chief U. S. Navy Bureau of Weapons Washington 25, D. C. ATTN: RMWC-322	143	Rome Air Development Center Griffiss Air Force Base Rome, New York ATTN: P. Sandler	155
Chief of Naval Operations Washington 25, D. C. ATTN: OP-07T10	144	The Martin Company Aerospace Division, Mail No. T-38 P.O. Box 179, Denver, Colorado 80201 ATTN: R. E. Compton, Jr.	156
Commander U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland ATTN: Technical Library	145	Space Technology Laboratories, Inc. 1 Space Park Redondo Beach, California ATTN: Leslie Hromas	157
Director U. S. Naval Research Laboratory Washington 25, D. C. ATTN: Code 2027	146	The Warner and Swasey Company Control Instrument Division 32-16 Downing Street Flushing 54, New York	158
New York University Department of Aero Engineering University Heights New York 53, New York ATTN: L. Arnold	147	University of California San Diego, California ATTN: Prof. N. M. Kroll	159
North American Aviation Space and Information Systems Division 12214 Lakewood Blvd Downey, California ATTN: E. Allen	148	University of California Lawrence Radiation Laboratory Livermore, California ATTN: C. Craig	160
Princeton University Princeton, New Jersey ATTN: Prof. E. Frieman	149	Scientific and Technical Information Facility P.O. Box 5700 Bethesda, Maryland	
ATTN: Prof. S. Bogdonoff	150	ATTN: NASA Representative (SAK/DL-639)	161, 162

DISTRIBUTION LIST (Concluded)

<u>Recipient</u>	<u>Copy No.</u>	<u>Recipient</u>	<u>Copy No.</u>
General Electric Company Re-entry Systems Department Missile and Space Division P. O. Box 8555 Philadelphia, Pennsylvania ATTN: Mr. H. W. Ridyard	163	* Commanding Officer U. S. Army Missile Command Redstone Arsenal, Alabama ATTN: SMIDW-B1 (C)	168
University of Michigan Radiation Laboratory 201 Catherine Ann Arbor, Michigan ATTN: R. J. Leite	164	**British Joint Mission British Embassy 3100 Massachusetts Avenue, N. W. Washington, D. C. ATTN: Mr. F. I. Reynolds, Defense Research Staff	169
Valley Forge Space Technical Center General Electric Company P. O. Box 8555 Philadelphia 1, Pennsylvania ATTN: J. Farber	165	**Australian Embassy 2001 Connecticut Avenue N. W. Washington, D. C. ATTN: D. Barnsley, Defense Research and Development Rep.	170
Director Weapons Systems Evaluation Group Pentagon, Room 1E-800 Washington 25, D. C.	166	Capt. L. L. Schoen, USAF USAF Technical Representative c/o GM Defense Research Laboratories	171
U. S. Army Liaison Office Canadian Armament Research and Development Establishment P. O. Box 1427 Quebec, P. Q., Canada ATTN: Lt. Col. E. W. Kreischer	167	GM Defense Research Laboratories	172 and above

* Unclassified reports only.

** Research reports on hypervelocity ranges and air and contaminant chemistry only - not included for analytical reports on U. S. missile data or classified reports.

Additional Distribution for Semiannual Reports only:

Office of Naval Research Department of the Navy Washington 25, D. C.	
ATTN: Dr. S. Silverman, Science Director	1 copy
ATTN: Dr. F. Isakson, Physics Branch	1 copy
ATTN: Mr. M. Cooper, Fluid Dynamics Branch	1 copy

UNCLASSIFIED

UNCLASSIFIED